

PRINTER SPECIFICATIONS (see usa.canon.com for full printer specs)**Print Head**

PF-06

Number of Nozzles

Matte Black: 5,120 Nozzles

Other Colors: 2,560 Nozzles per Color

Droplet Size

5 Picoliter

Ink Type

Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

Ink Tank

Shipped with Printer: MBK (130 ml) BK, C, M, Y (90 ml)

Replacement: PFI-120 (130 ml) or PFI-320 (300 ml)

Printer RAM

TM-305: 128 GB (2 GB Physical Memory)

TM-200/300: 2 GB

Hard Drive

TM-305: 500 GB

Media Feed

Roll Feed: One Roll, Top-loading, Front Output

Cut Sheet: Top-loading, Front Output

Media Width

TM-305/300

Roll Feed: 8"-36" (203 mm - 914 mm)

Cut Sheet: 8"-36" (203 mm - 914 mm)

TM-200

Roll Feed: 8"-24" (203 mm - 610 mm)

Cut Sheet: 8"-24" (203 mm - 610 mm)

Media Cutter

Durable Dual-Blade Rotary Cutter

Media Thickness

0.07 - 0.8 mm

Media Core Sizes

2" and 3" Core Adapters Included

Maximum Roll Outer Diameter

5.9" (150 mm)

Media Output

TM-305: Flat Stacking Basket (standard)

TM-300/200: Basket (standard)

Printing Software Utilities

Accounting Manager, Apple AirPrint, Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist Lite for Windows, Canon PRINT Inkjet Selphy, Easy-Photo PrintEditor,† Optimized Driver for AutoCAD, Free Layout

Operating System

Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5-v10.12x

Print Language

TM-305: SGRaster, HP-GL/2, HP RTL, JPEG, PDF

TM-300/200: SGRaster, HP-GL/2, HP RTL, JPEG

Interface

TM-305: Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)■

Direct USB Thumb Drive

TM-300/200: Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)■

Power Supply

AC 100-240V (50-60 Hz)

Power Consumption

Maximum: 69 W or Less

Standby: 3.6 W or Less

Power Off: 0.3 W or Less (Executive Order Compliant)

Certifications

Environmental Certifications

ENERGY STAR® (Worldwide)

Operational Environment

Temperature: 59° - 86° F (15° - 30° C)

Relative Humidity: 10 - 80% (No Condensation)

Printer Dimensions (H x W x D) and Weight

(With Basket Opened)

TM-305: 42" x 51" x 35" Approx 134 lb.

TM-300: 42" x 51" x 34" Approx 130 lb.

TM-200: 42" x 38" x 34" Approx 112 lb.

Package Dimensions (H x W x D) and Weight

With Stand, Basket, and Pallet

TM-305: 38" x 58" x 36" Approx. 231 lb.

TM-300: 38" x 58" x 36" Approx. 229 lb.

TM-200: 38" x 45" x 36" Approx. 187 lb.

Options

TM-200: 2"/3" Roll Holder Set (RH2-28)

TM-305/300: 2"/3" Roll Holder Set (RH2-35)

PosterArtist

User-Replaceable Items

- Ink Tank (PFI-120/PFI-320)
- Print Head (PF-06)
- Maintenance Cartridge (MC-31)
- Cutter Blade (CT-08)

What's In The Box

Printer, Basket, Stand, 2"/3" Core Media Spool (Adapters Included), Power Cord, Tools and Screws, Print Head, Maintenance Cartridge (Installed), 5 Ink Tanks (130 ml: MBK, 90 ml: BK/C/M/Y), Sample Heavyweight Coated Paper (A2/2 Sheets), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, iWR Service Terms Leaflet, User Manual, Quick Setup Guide, User Software CD for Windows (Printer Driver Utilities), PosterArtist Lite CD, User Registration Card

T36 SCANNER SPECIFICATIONS

Scan Speed**

- 48-bit Full Color @ 200 dpi: 6" per second
- 16-bit Grayscale and Monochrome @ 200 dpi: 13" per second

Scan Modes

- 16.7-million Color RGB (24-bit)
- 256-level Grayscale (8-bit)
- Black and White (1-bit)

Color Space

sRGB

Maximum Resolution

1200 dpi (optical)

Scan Accuracy

+/- 0.1%; +/- 1 pixel

Maximum Scan Width

36"

Maximum Media Width

38"

Maximum Scan Length

315" (JPEG/PDF), 598" (TIFF)

Maximum Media Thickness

0.079" (2 mm)

Media Feed System

Adaptive CIS media focus management and media guide mechanism; intuitive face-up, front-loading, and front/rear-exit media path; automatic media size detection with optical media sensors

Digital Imaging Technology

Contact Image Sensor (CIS) Technology (SingleSensor Assembly)

- 48-bit RGB digital color image capture
- 16-bit grayscale image capture
- Panchromatic monochrome and black and white
- Bi-directional extra long-life LED light system for optimum object illumination and instant-on scanning capability

Digital Image Processing

- 2D Intelligent Adaptive Thresholding (IAT) (1-bit mode)
- Fixed Threshold Black and White (1-bit mode)

User Status and One-Touch Operation

Right-side-mounted control panel; walk-up operation and user selection of stop, forward, and rewind

Included Software

- SmartWorks MFP Scan-to-Copy/File/Email with Real-time Image Viewer; supports TIFF, JPEG, TIFF G4, and PDF

Operating System

Windows 10 Enterprise LTSB (x64)

Scanner Interface Kit

Superspeed USB 3.0 (PC Connector Compatible with USB 2.0 and USB 3.0 sockets)

Operating Environment

10 - 35°C, 35-80% RH, Non-condensing

External Power Supply

100-240 VAC Autosensing +/- 10%, 50-60Hz

Scanner Power Consumption

- 53 Wh (scanning)
- 5 Wh (standby)

Compliances

VCCI, CB, CE, FCC, UL, RoHS, ENERGY STAR®

Scanner DimensionsHeight: 6.3"
Width: 43.6"
Depth: 14.4"**Scanner Weight**

Approx. 33.1 lb.

What's In The Box?

- T36 Scanner with Power Cord, USB 3.0 Cable
- Power Supply
- Ethernet Cable
- Stand
- (2) Paper Edge Guides
- (3) Document Return Guides
- All-in-One Touch Screen Computer
- USB Drive with SmartWorks MFP Software, Scanner User Manual, and Quick Start Guide
- Calibration Target
- T36 Scanner Quick Start Guide

† To be supported in December 2018.

■ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

■ The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types.